

# Ubiflex Finio 400mm x 5m Grey

Article number: 535213

## Product introduction

Ubiflex Finio is a high quality non-lead flashing, which can be used to waterproof buildings. It is lightweight and malleable, allowing it to be easily formed into an infinite variety of shapes to form stepped flashings, abutment flashings, chimney flashings, pitched roof valley liners, dormer window flashings, rooflight and solar panel flashings.

Ubiflex Finio features a full adhesive backside protected with a two-part removable film for convenient handling during application. Additionally the rolls are equipped with two butyl adhesive strips to ensure perfect adhesion to most materials. Ubiflex Finio can easily be formed by hand and as required be finished with a roller.




- Easy and quick installation
- Adhesion to most materials
- Double adhesion for high-performance and durability
- Vulcanises
- Environmentally friendly; non-toxic and recyclable

## Safety, Health & Environment

Ubiflex Finio is non-toxic, non-hazardous to human and environment.

## Additional information

For a perfect self-welding effect, the overlap between two pieces of Ubiflex Finio must never be less than 50 mm. Ubiflex Finio does not react to aluminum, copper and zinc. However, if Ubiflex Finio is likely to come in contact with aggressive chemicals during work or maintenance, first test on a piece of material before proceeding. If in doubt contact your reseller.



# Ubiflex Finio 400mm x 5m Grey

Article number: 535213

## Technical specifications

Specifications	
Technical	
Colour	Grey
Colour indication	RAL 7012
Material	Polyisobutylene (PIB)
Performance	
Temperature resistance (min.)	-30 °C
Temperature resistance (max.)	140 °C
Reinforcement	<input checked="" type="checkbox"/>
Self adhesive	<input checked="" type="checkbox"/>
Stretch length	97 %
Stretch width	20 %
Installation temperature (min.)	5 °C
Installation temperature (max.)	50 °C
Dimensions	
Length gross	5 m
Length gross	5000 mm
Width	400 mm
Thickness	1.9 mm
Net weight	5.6 kg

# Ubiflex Finio 400mm x 5m Grey

Article number: 535213

## Technical details

### Watertightness

watertight EN 1928

### Bending characteristics (after 10 times folding)

	23°C	50%
longitudinal	✓	✓
transverse	✓	✓
	EN 495-5:2013	

### Tensile strength

longitudinal	225 N
transverse	675 N
	EN 12311-2:2013

### UV resistance

excellent EN 1297:2004

### Sensitivity to thermal aging and moisture

not sensitive EN ISO 16536:2019

### Resistance against corrosion

not sensitive EN ISO 6988

### Fire Rating

Class E EN 13501-1