

UB19 HOODED SLATE VENT

Introduction

The UB19 is a streamlined hood suitable for most finishes and has a free vent area of 22,000mm². This unit allows less vents to be used to meet British standards due to the higher free vent area. UB19's are suitable for roof pitches from 23°

Product features and benefits

- 22,000mm² large free vent area
- Injection moulded construction

Application

- High or low level roof void ventilation
- Mechanical extraction when used with the Felt Sleeve and Stepped Adaptor
- Minimum pitch of 23°

Material

- PVC-U and Polyethylene

Dimensions

- NJ/UB19 L: 500mm x W: 250mm
- NS/UB19 L: 600mm x W: 300mm
- NL/UB19 L: 600mm x W: 450mm

Weight

- NJ/UB19 0.62kg
- NS/UB19 0.78kg
- NL/UB19 1.11kg

Packaging

- 6 per box for NJ and NS
- 4 per box for NL



Colours

- Anthracite

Product Code

- 500mm x 250mm (NJ) 100152291424
- 600mm x 300mm (NS) 100152293439
- 600mm x 450mm (NL) 100152293484

NB: To convert to a terminal please add the Felt Sleeve and Stepped Adaptor 50544180

Performance

- Provides 22,000mm² free vent area

Spacing	5mm	10mm	25mm
M Centres	4.4	2.2	0.880