# OFT 1 Flat Roof Vent/Terminal

ubbink
Build smart.

### Product features and benefits
- Large free vent area/Low Pa resistance

### Application
- Allows termination through a flat roof to ducting up to 166mm
- With the spigot cut to 50mm allows ventilation into a flat roof to meet the requirements of

**OFT 1 169931 110mm & 169933 160mm**

**OFT 1 Asphalt flange**

**EPDM**



**PVC**

**Bitumen**

### Material Per Roof Type
- Asphalt: Polyethylene/Aluminium
- Felt: Polyethylene
- EPDM: Polyethylene/Aluminium/EPDM
- Bitumen: Polyethylene/Aluminium/Bitumen
- PVC: Polyethylene/Aluminium/PVC
- Polyethylene material is fire retardant

### Colours
- Black (Stack section only)

### Product Codes

| | Asphalt | Felt | EPDM | Bitumen | PVC |
|---|---|---|---|---|---|
| OFT1 110mm | 169931 | 169931 | - | - | - |
| OFT1 131mm | | - | 185673 | 185675 | 185677 |
| OFT1 166mm | | 169933 * | 185690 | 185692 | 185694 |

* 169933 has a 160mm diameter

### Weights

| | Asphalt | Felt | EPDM | Bitumen | PVC |
|---|---|---|---|---|---|
| OFT1 110mm | 1.06 kg | 1.72kg | - | - | - |
| OFT1 131mm | | - | 1.53 kg | 2.15 kg | 1.56 kg |
| OFT1 166mm | | 2.4 kg | 2.46 kg | 3.09 kg | 2.51 kg |

### Dimensions and Performance

| Diameter mm | Height Above Roof mm | Flange Dia mm | Depth Below Roof mm | Free vent area mm² | * Pa Resistance Extract |
|---|---|---|---|---|---|
| 110mm | 220 | 330 | 600 | 8,400 | 5.9 |
| 131mm | 500 | 450 | 350 | 12,000 | 1.1 |
| 166 mm | 522 | 450 | 350 | 18,750 | 1.0 |
| 160mm | 240 | 363 | 600 | 18,750 | 3.0 |

- 131/110 reducer (147059)
- 131/125 reducer (147062)
- 167/149 reducer (147064)

NB Reducers available

© UBBINK • Designs and specifications are subject to change without notice