

EXTREME FIX

All-round adhesive and joint sealant



Product information

Extreme Fix is a high quality and universal adhesive and sealant for bonding Ubiflex Extreme flashing to many surfaces including natural stone. Extreme Fix is based on hybrid technology which cures under influence of humidity to form a durable elastic bond.

Benefits

- Extreme adhesion on most building materials, if damp
- UV and weather resistant
- Can be used as both adhesive and joint sealant
- Plasticizer free
- No staining or discolouring on natural stone

Applications

Extreme Fix has been developed as a universal sealant for bonding and sealing Ubiflex Extreme flashing to most construction materials, e.g. natural stone, ceramics, concrete, glass, PU, uPVC, hard plastics, enamel, metals and wood. It can be used for sealing and bonding in cold applications.

Directions of use

For general applications: Apply a bead on the surface and press the pre-dressed Ubiflex Extreme softly into position.

For profiled tiled roofs: Cut back the nozzle with +/- 3 cm if desired. Apply a 6 to 10 mm bead in every valley of the profiled tiles and press the pre-dressed Ubiflex Extreme softly into position. As an alternative, dots on every top can be used for steep roofs in milder wind zones.

As a joint sealant: The ratio between the joint depth and joint width should be 1:1 with a minimum of 5 mm.



EXTREME FIX

All-round adhesive and joint sealant



Additional information

| | | |
|--|-------------------|------------|
| 100 % Modulus | N/mm ² | 1,60 MPa |
| Application Rate | g/min @3mm/4bar | 150 |
| Application Temperature | +5°C till +40°C | |
| Base | Hybrid | |
| Curing Time | ± 2-3mm/24 hours | |
| Density | 1,42 g/ml | |
| Elongation at Break | 300 % | |
| Flow | ISO 7390 | <2 mm |
| Frost Resistance during transportation | till -15°C | |
| Shore-A hardness | DIN 53505 | 60 Shore A |
| Skin Formation | @23°C/55 % RH | 10 min |
| Temperature Resistance | -40°C till +90°C | |
| Tensile Strength | N/mm ² | 2,60 MPa |

Limitations

- Not suitable for PE, PP, PC, PMMA, PTFE, neoprene and bituminous surfaces
- Not suitable for continuous water load
- Not suitable for glazing joints
- Not suitable in combination with chlorides (pools)

Surface Preparations and Finishing

Application temperature +5°C to +40°C (both environment and surface). Surfaces must be clean, dust free, sound and reasonably dry. Extreme Fix adheres without the use of a primer to most non porous substrates. Porous surfaces to be pre-treated with a suitable primer. Always test adhesion, cleaner and/or primer prior to application to unknown materials.

Cleaning

Uncured material and tools can be cleaned with heavy duty wipes.

Cured material can only be mechanically removed.

To avoid sticking to the hands the use of gloves is recommended.

Colour

Grey

Packaging

Cartridge 290 ml

Shelf Life

18 months shelf life after production date, if stored in a dry place between +5°C and +25°C in its original packaging.

Certifications

| | |
|--------------------------|---------------|
| EN 15651-1: F-EXT-INT-CC | (klasse 20HM) |
| EN 15651-3: S | (klasse XS3) |

Health & Safety

Product Health and Safety Data Sheet must be read and understood before use. These are available on request and via the Ubbink websites.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Ubbink. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Ubbink's written consent.

The technical information in this document serves as an indication and is non-exhaustive. Ubbink is not liable for any damage, either direct or indirect, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired.

Ubbink reserves the right to amend the wording of this document. Ubbink cannot be held liable for any damage, either direct or indirect, due to the use of the product depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

