

Ubiflex Finio 250mm x 5m Grey

Article number: 535201

Product introduction

Ubiflex Finio is a high quality non-lead flashing, which can be used to waterproof buildings. It is lightweight and malleable, allowing it to be easily formed into an infinite variety of shapes to form stepped flashings, abutment flashings, chimney flashings, pitched roof valley liners, dormer window flashings, rooflight and solar panel flashings.

Ubiflex Finio features a full adhesive backside protected with a two-part removable film for convenient handling during application. Additionally the rolls are equipped with two butyl adhesive strips to ensure perfect adhesion to most materials. Ubiflex Finio can easily be formed by hand and as required be finished with a roller.




- Easy and quick installation
- Adhesion to most materials
- Double adhesion for high-performance and durability
- Vulcanises
- Environmentally friendly; non-toxic and recyclable

Safety, Health & Environment

Ubiflex Finio is non-toxic, non-hazardous to human and environment.

Additional information

For a perfect self-welding effect, the overlap between two pieces of Ubiflex Finio must never be less than 50 mm. Ubiflex Finio does not react to aluminum, copper and zinc. However, if Ubiflex Finio is likely to come in contact with aggressive chemicals during work or maintenance, first test on a piece of material before proceeding. If in doubt contact your reseller.



Ubiflex Finio 250mm x 5m Grey

Article number: 535201

Technical specifications

| Specifications | |
|---------------------------------|-------------------------------------|
| Technical | |
| Colour | Grey |
| Colour indication | RAL 7012 |
| Material | Polyisobutylene (PIB) |
| Performance | |
| Temperature resistance (min.) | -30 °C |
| Temperature resistance (max.) | 140 °C |
| Reinforcement | <input checked="" type="checkbox"/> |
| Self adhesive | <input checked="" type="checkbox"/> |
| Stretch length | 97 % |
| Stretch width | 20 % |
| Installation temperature (min.) | 5 °C |
| Installation temperature (max.) | 50 °C |
| Dimensions | |
| Length gross | 5 m |
| Length gross | 5000 mm |
| Width | 250 mm |
| Thickness | 1.9 mm |
| Net weight | 3.5 kg |

Ubiflex Finio 250mm x 5m Grey



Article number: 535201

Technical details

Watertightness

watertight EN 1928

Bending characteristics (after 10 times folding)

| | 23°C | 50% |
|--------------|------|-----|
| longitudinal | ✓ | ✓ |
| transverse | ✓ | ✓ |

EN 495-5:2013

Tensile strength

| | |
|--------------|-------|
| longitudinal | 225 N |
| transverse | 675 N |

EN 12311-2:2013

UV resistance

excellent EN 1297:2004

Sensitivity to thermal aging and moisture

not sensitive EN ISO 16536:2019

Resistance against corrosion

not sensitive EN ISO 6988

Fire Rating

Class E EN 13501-1