

Eaves Guard

Introduction

The Ubbink Eaves Guard is designed for use in both refurbishment projects and new build to provide an effective level of eaves protection.

Available in 1.5m lengths, the rigid pre-formed strips are suitable for use in roof pitches of 15 – 70 degrees. On existing buildings, Eaves Guard can be used to replace rotted gutter felt with the minimum of disruption to the existing slate or tile roof covering.

In new build situations, the preformed Eaves Guard strip directs water away from the underlay and into the gutter. At the same time it provides an effective underlay support flap, preventing ponding of the underlay behind the fascia board. Eaves Guard is ideal for use with the new generation of lightweight, high performance underlays, which are not suitable for forming a drip into the gutter.

Eaves Guard is fixed to the top of the fascia with clout nails. If a plastic fascia is used which will not support clout nails, Eaves Guard may be fixed to a batten behind the fascia.



Product features and benefits

- Protects the roofing underlay from UV degradation
- Prevents ponding at the rear of the fascia board
- Directs water away from the underlay into the gutter

Application

- New build and refurbishment

Dimensions

- 1.5m length

Weight

- 1.5m 0.9kg per unit & 18kg per pack

Colours

- Black

Product Code

- 1.5m 294254

Packaging

- 20 per pack
- 1.5m 500 per pallet

Material

- PVC-U