


Air Excellent AE55SC Semi-Rigid Duct Anti-Microbial & Anti-Static 30m

Article number: 188373



Product introduction

An Air Excellent semi-rigid plastic duct 130*60mm with Anti-Microbial and Anti-Static additives.

- Modular manifolds, which can be used with all 6 duct types
- Semi-rigid plastic ducts on a roll and airtight mechanical connections, which are extremely easy to install
- Low system pressure loss due to radial design
- Airtight (class D/ATC 2 up +/- 2000 Pa) thanks to mechanical connections, which minimises fan energy use and sound production
- TÜV SÜD and ISEGA tested and certified, REACH compliant



Product dimensions



Technical specifications

Specifications	
Technical	
Colour	Green
Material	PE
Anti static	<input checked="" type="checkbox"/>
Antimicrobial	<input checked="" type="checkbox"/>

Air Excellent AE55SC Semi-Rigid Duct Anti-Microbial & Anti-Static 30m

Article number: 188373


Technical specifications (continuation)

Technical	
Outer height	60 mm
Outer width	130 mm
Performance	
Temperature resistance (min.)	-20 °C
Temperature resistance (max.)	60 °C
Reaction to fire: Euro class	E
Installation temperature (min.)	5 °C
Installation temperature (max.)	50 °C
Dimensions	
Length gross	30000 mm
Width	133 mm
Height	60 mm
Net weight	13.95 kg

Air Excellent AE55SC Semi-Rigid Duct Anti-Microbial & Anti-Static 30m

Article number: 188373

Technical details




	AE55SC [/m]		AE55SC Vertical		AE55SC Horizontal	
Radius [mm]	0		200		400	
Zeta [-]	0		1,64		0,68	
Duct runs	1		1		1	
Qv [m³/h]	v [m/s]	Δp [Pa]	v [m/s]	Δp [Pa]	v [m/s]	Δp [Pa]
0	0,0	0,0	0,0	0,0	0,0	0,0
5	0,3	0,1	0,3	0,1	0,3	0,0
10	0,5	0,2	0,5	0,3	0,5	0,1
15	0,8	0,3	0,8	0,6	0,8	0,2
20	1,0	0,5	1,0	1,0	1,0	0,4
25	1,3	0,7	1,3	1,6	1,3	0,7
30	1,5	0,9	1,5	2,3	1,5	0,9
35	1,8	1,2	1,8	3,1	1,8	1,3
40	2,1	1,5	2,1	4,1	2,1	1,7
45	2,3	1,8	2,3	5,2	2,3	2,1
50	2,6	2,1	2,6	6,4	2,6	2,6
55	2,8	2,5	2,8	7,7	2,8	3,2
60	3,1	2,9	3,1	9,2	3,1	3,8
65	3,3	3,3	3,3	10,8	3,3	4,5
70	3,6	3,8	3,6	12,5	3,6	5,2
75	3,8	4,2	3,8	14,3	3,8	5,9
80	4,1	4,8	4,1	16,3	4,1	6,8
85	4,4	5,3	4,4	18,4	4,4	7,6
90	4,6	5,8	4,6	20,6	4,6	8,5
95	4,9	6,4	4,9	23,0	4,9	9,5
100	5,1	7,1	5,1	25,5	5,1	10,6

Air Excellent AE55SC Semi-Rigid Duct Anti-Microbial & Anti-Static 30m

Article number: 188373

Technical details






AE55SC [/m]		AE55SC Vertical		AE55SC Horizontal		
Radius [mm]	0		200		400	
Zeta [-]	0		1,64		0,68	
Duct runs	2		2		2	
Qv [m³/h]	v [m/s]	Δp [Pa]	v [m/s]	Δp [Pa]	v [m/s]	Δp [Pa]
0	0,0	0,0	0,0	0,0	0,0	0,0
5	0,1	0,0	0,1	0,0	0,1	0,0
10	0,3	0,1	0,3	0,1	0,3	0,0
15	0,4	0,1	0,4	0,1	0,4	0,1
20	0,5	0,2	0,5	0,3	0,5	0,1
25	0,6	0,3	0,6	0,4	0,6	0,2
30	0,8	0,3	0,8	0,6	0,8	0,2
35	0,9	0,4	0,9	0,8	0,9	0,3
40	1,0	0,5	1,0	1,0	1,0	0,4
45	1,2	0,6	1,2	1,3	1,2	0,5
50	1,3	0,7	1,3	1,6	1,3	0,7
55	1,4	0,8	1,4	1,9	1,4	0,8
60	1,5	0,9	1,5	2,3	1,5	0,9
65	1,7	1,1	1,7	2,7	1,7	1,1
70	1,8	1,2	1,8	3,1	1,8	1,3
75	1,9	1,3	1,9	3,6	1,9	1,5
80	2,1	1,5	2,1	4,1	2,1	1,7
85	2,2	1,6	2,2	4,6	2,2	1,9
90	2,3	1,8	2,3	5,2	2,3	2,1
95	2,4	2,0	2,4	5,7	2,4	2,4
100	2,6	2,1	2,6	6,4	2,6	2,6
105	2,7	2,3	2,7	7,0	2,7	2,9
110	2,8	2,5	2,8	7,7	2,8	3,2
115	2,9	2,7	2,9	8,4	2,9	3,5
120	3,1	2,9	3,1	9,2	3,1	3,8
125	3,2	3,1	3,2	9,9	3,2	4,1

Air Excellent AE55SC Semi-Rigid Duct Anti-Microbial & Anti-Static 30m

Article number: 188373

Technical details



	AE55SC [/m]		AE55SC Vertical		AE55SC Horizontal	
Radius [mm]	0		200		400	
Zeta [-]	0		1,64		0,68	
Duct runs	2		2		2	
Qv [m³/h]	v [m/s]	Δp [Pa]	v [m/s]	Δp [Pa]	v [m/s]	Δp [Pa]
130	3,3	3,3	3,3	10,8	3,3	4,5
135	3,5	3,5	3,5	11,6	3,5	4,8
140	3,6	3,8	3,6	12,5	3,6	5,2
145	3,7	4,0	3,7	13,4	3,7	5,5
150	3,8	4,2	3,8	14,3	3,8	5,9
155	4,0	4,5	4,0	15,3	4,0	6,3
160	4,1	4,8	4,1	16,3	4,1	6,8
165	4,2	5,0	4,2	17,3	4,2	7,2
170	4,4	5,3	4,4	18,4	4,4	7,6
175	4,5	5,6	4,5	19,5	4,5	8,1
180	4,6	5,8	4,6	20,6	4,6	8,5
185	4,7	6,1	4,7	21,8	4,7	9,0
190	4,9	6,4	4,9	23,0	4,9	9,5
195	5,0	6,7	5,0	24,2	5,0	10,0