## 2024 Ubbink. All rights reserved.1 Content is subject to change without notice. Availability and configurations may differ per country. 1 UB-20-12-2024-1NT-EN

### **Air Excellent AE55SC Connector**




Article number: 188156


### **Product introduction**

An AE55SC duct accessory used to connect AE55SC ducts. Use 2 AE55SC seal & click rings to connect the ducts to it.

- Modular manifolds, which can be used with all 6 duct types
- Semi-rigid plastic ducts on a roll and airtight mechanical connections, which are extremely easy to install
- Low system pressure loss due to radial design
- Airtight (class D/ATC 2 up +/- 2000 Pa) thanks to mechanical connections, which minimises fan energy use and sound production
- TÜV SÜD and ISEGA tested and certified, REACH compliant

### **Product dimensions**





### **Performance**

Airtightness Class D for Air Excellent ductwork, Air Excellent ductwork accessories and the Air Excellent plastic distribution boxes. Tested according to TÜV SÜD Standard TAK 01-2013 (system pressure: + 2000 Pa/– 2000 Pa)







# © 2024 Ubbink. All rights reserved.1 Content is subject to change without notice. Availability and configurations may differ per country.1 UB-20-12-2024-INT-EN

## **Air Excellent AE55SC Connector**



Article number: 188156

### **Technical specifications**

Specifications	
Technical	
Colour	Green
Material	PP
Anti static	$\checkmark$
Antimicrobial	$\checkmark$
Performance	
Temperature resistance (min.)	-20 °C
Temperature resistance (max.)	60 °C
Reaction to fire: Euro class	E
Dimensions	
Length gross	102 mm
Width	148 mm
Height	71 mm
Net weight	0.09 kg