# Ubbink Universal Dry Verge System



## Introduction

The Ubbink Universal Dry Verge is a mortar free system to mechanically fix the verge tiles according to BS5534 and meets all NHBC regulations giving a 10 year warranty. It is quick and easy to install.

The system offers integral solutions for a secure fixing to the roof. The starter unit at the eaves offers three different installation strategies, depending on the roof construction available:

- Fixing to the barge board
- Fixing to the fascia board
- Fixing to the lowest batten

## **Key Features and Benefits**

- Universal ambi unit, resulting in less stock holding
- Each ambi unit has a water drip channel,
  preventing water staining
- Suits popular profile roof tiles with a batten gauge range of 255mm to 355mm
- Suits the thin leading edge tile (additional cutting is required on ambi unit tabs)
- The starter unit gives a positive fixing point for the system and can be installed either with or without the gutter in place
- The batten bracket gives a secure fixing to the end of the batten. Also no measuring is required for the 30mm overhang of the batten as the batten bracket abuts a flush cut batten
- Suits roof pitches up to 55°

## Material

## Dry Verge System Components

- Ambi verge units
- Half round/segmental or universal angled ridge end cap
- Starter unit (incorporates closure)
- Batten bracket

### Colours

• Grey , Brown and Terracotta

# Weights and Packaging

Ambi verge units		Ambi verge units	
Material: Colour: Surface finish:	PP talc, UV resistant Grey and brown Matt	Packaging: Single Unit weight:	Bags of 10, box of 50 0.215 KG
Ridge end caps		Ridge end caps	
Material: Colour: Surface finish:	PP talc, UV resistant Grey and brown Matt	Packaging: Single Unit weight:	Box of 10 0.17 KG
Brackets		Brackets	
Material: Colour: Surface finish:	PP talc Grey Smooth	Packaging: Single Unit weight:	Bags of 10, box of 50 0.03 KG
Starter units		Starter units	
Material: Colour: Surface finish:	PP talc Grey Smooth	Packaging: Single Unit weight:	Bags of 2, box of 20 0.045 KG

Ubbink UK • info.@ubbink.co.uk • www.ubbink.co.uk