

Aerfoam Duct 125x2000mm



Article number: 188202

Product introduction

The Aerfoam 125 mm Duct is made of expanded polyethylene (EPE), which minimises the risk of condensation and energy loss. It is very light and extremely easy and safe to install. All Aerfoam parts connect to each other using strong, airtight mechanical connections. They can also be securely mounted to walls or ceilings using brackets. Aerfoam is ideal for both central mechanical ventilation and domestic hot water heat pump systems.

- Insulated to minimise the risk of condensation and energy loss.
- Easy mechanical connection and mounting.
- Lightweight and easy to cut, ensuring quick installation.
- Impact resistant.

Product dimensions



Aerfoam Duct 125x2000mm

Article number: 188202

Technical specifications

Specifications	
Technical	
Colour	Grey
Insulated	☒
Diameter inner	125 mm
Diameter outer	157 mm
Insulation thickness	16 mm
Performance	
Insulation performance	0.041 W/m.K
Temperature resistance (min.)	-30 °C
Temperature resistance (max.)	60 °C
Zeta supply 1 connection	0.22
Zeta extract 1 connection	0.22
Dimensions	
Length gross	2000 mm
Width	157 mm
Height	157 mm
Net weight	0.4 kg

Aerfoam Duct 125x2000mm

Article number: 188202

Technical details

Aerfoam Duct		
Diameter	125	
Qv [m³/h]	v [m/s]	Δp [Pa]
100	2,3	1,0
200	4,5	2,7
300	6,8	6,1
400	9,1	10,8
500	11,3	16,9
600	13,6	24,3