

# UB41 Hooded Tile Terminal Universal

## Introduction

The UB41 is a Universal Service Terminal for use in most tiled and slated pitched roofs without the need to identify the make or design of the tiles or slates. The unit comprises a streamlined hood on a circular upstand, a 500mm x 500mm Ubiflex flashing skirt and stepped adaptor which allows connections from 100mm to 160mm diameter ducting. The unit may also be used to terminate soil & vent pipes where an external pressure test is not required.

## Product features and benefits

- Up to 18,750mm<sup>2</sup> large free vent area
- Large diameter spigot c/w Adaptor to accept ducting of 100/110/125/150mm (160mm does not need an adaptor)
- Easy to install
- The Ubiflex flashing allows fitting into most tiles/slates.

## Application

- Mechanical extraction
- Minimum pitch of 22.5°
- The adaptor is cut off at the required diameter and attached to the undertile spigot with solvent weld/PVC glue

## Material

- PVC-U and Ubiflex & polypropylene

## Dimensions

- 500mm x 500mm skirt
- Stepped Adaptor— H: 215mm



Terracotta



Anthracite



Sepia



Red

## Colours & Product Code

- Red - 100130172069 (Terracotta Ubiflex)
- Terracotta - 100130172067 (Terracotta Ubiflex)
- Anthracite - 100130172063 (Black Ubiflex)
- Sepia - 100130172066 (Black Ubiflex)

## Weight & Packaging

- 1.53kg per unit
- 1 per box

Diameter (mm)	Free Vent Area (mm <sup>2</sup> )	Pressure/Airflow Resistance (Pascals)	
		100m <sup>3</sup> /h	225m <sup>3</sup> /h
100	7,850	7.5	7.5
110	8,850	4.5	16.0
125	12,250	5.3	24.0
150	17,750	6.5	31.0
160	18,750	6.5	31.0