

OFT 5 Insulated Flat Roof Terminals

Product features and benefits

- Large free vent area/Low Pa resistance
- Fully insulated to the cowl
- 2 piece stack aluminum flange

Application

- Allows termination through a flat roof void to ducting up to 180mm when used with reducers

Material Per Roof Type

- Asphalt: Polyethylene/Aluminium
- EPDM: Polyethylene/Aluminium/EPDM
- Bitumen: Polyethylene/Aluminium/Bitumen
- PVC: Polyethylene/Aluminium/PVC

Polyethylene material is fire retardant



Colours

- Black (Stack section only)

Product Codes

| | Asphalt | EPDM | Bitumen | PVC |
|------------|----------|----------|----------|----------|
| OFT5 125mm | 50147225 | 50147230 | 50147235 | 50147240 |
| OFT5 150mm | 50147250 | 50147255 | 50147260 | 50147265 |
| OFT5 180mm | 50147280 | - | - | - |

Weights

| | Asphalt | EPDM | Bitumen | PVC |
|------------|---------|---------|---------|---------|
| OFT5 125mm | 2.26 kg | 3.49 kg | 3.54 kg | 2.96 kg |
| OFT5 150mm | 2.4 kg | 2.49 kg | 3.5 kg | 2.9 kg |
| OFT5 180mm | 2.79 kg | - | - | - |

Dimensions and Performance

- *Reading at 200m³/h

| Diameter mm | Height above roof mm | Flange Dia mm | Depth below roof mm | Free vent area mm ² | Pa resistance Extract |
|-------------|----------------------|---------------|---------------------|--------------------------------|-----------------------|
| 125mm | 522 | 490 | 608 | 11300 | 5.3 |
| 150mm | 522 | 490 | 608 | 14400 | 1.3 |
| 180mm | 560 | 495 | 699 | 19100 | 1.3 |