

UB62 IN-LINE TILE VENT DOUBLE PANTILE (MEN)

Introduction

The UB62 in-line tile vent offers high performance whilst retaining the aesthetics of the roof design. It is designed to provide ventilation of the roof space, either at high or low levels. UB62s are suitable for pitches from 25-55 degrees. and may be used to supplement or replace other ventilation such as dry ridge, abutment or eaves systems. They are also suitable for ventilation of compartmental roof spaces, such as fire walls. The UB62 provides up to 15,000mm² of free vent area, and has a large insect and vermin grille.

Product features and benefits

- High performance yet aesthetically pleasing
- Injection moulded construction
- Built in spigot allows direct ventilation into roof

Application

- High or low level roof void ventilation
- Mechanical extraction when used with the stepped adaptor
- Minimum pitch 25°

Material

- Polypropylene

Dimensions

- L: 420mm x W: 330mm

Weight

- 0.73kg (including clip) per unit
- 5.84kg per box

Packaging

- 6 per box



Performance

- Provides 15,000mm² free vent area

Product code

- Anthracite 294795
- Sepia 294880
- Terracotta 294801
- Red 294870

NB: With the use of a stepped adaptor 544180, the UB62 can also be used for mechanical extraction or with soil pipes for removal of foul air, as well as bathroom fans to small kitchen extracts.

Spacing	5mm	10mm	25mm
M Centres	3.0	1.5	0.6