

# OFT 4 Uninsulated Flat Roof Terminals

## Product features and benefits

- Large free vent area/low Pa resistance  
The pipework above the roofline is twin walled and incorporates an integral condensation drain

## Application

- Allows termination through a flat roof to ducting up to 166mm

## Material Per Roof Type

- Asphalt: Polyethylene/Aluminium
- EPDM: Polyethylene/Aluminium/EPDM
- Bitumen: Polyethylene/Aluminium
- Bitumen PVC: Polyethylene
- Aluminium/PVC **Polyethylene material is a fire retardant**

## Product Codes



## Colours

Black (Stack section only)

	ASPHALT	EPDM	BITUMEN	PVC
OFT4 110mm	50185736	-	-	-
OFT4 131mm	50147004	50147006	50147008	50147010
OFT4 166mm	50147138	50147040	50147042	50147044

## Weights

	ASPHALT	EPDM	BITUMEN	PVC
OFT4 110mm	1.78 kg	-	-	-
OFT4 131mm	1.73 kg	1.68 kg	2.3 kg	1.72 kg
OFT4 166mm	2.67 kg	2.66 kg	3.28 kg	2.71 kg

## Dimensions and Performance

\*Reading at 225mm<sup>3</sup>/h

Diameter mm	Height above roof mm	Flange mm	Depth below roof mm	Free vent area mm <sup>2</sup>	Pa Resistance Extract
110mm	395	350	350	8,400	<1.0
131mm	450	450	350	12,000	<1.0
166mm	450	450	510	18,750	<1.0

## NB Reducers available

- 131/110 (147059)
- 131/125 (147062)
- 167/147 (147064)