

Dry Ridge Ventilation System Black

Article number: 294350

Product overview

The Ubbink Flexible Dry Ridge Kit is a mortar free system to mechanically fix the ridge tiles according to BS5534. It is easy to install under most weather conditions and the kit offers enough components for a typical ridge of up to 6m. The kit provides high level ventilation, is watertight and has a wind uplift to suit most UK properties.

This is a truly ventilating ridge kit for flat interlocking, slate and plain tile as well as profiled tiles.

It matches a comprehensive range of ridge tiles, including:

- Redland Universal Angle
- Half Round/Segmental
- Marley Modern
- Easy and quick to install
- Independently tested by the BRE to meet British Standards
- High performing ridge roll offering true ventilation

Applications

Hip trays are available in Black 1200mm long and are quick and easy to install. There is no need for mortar when installing and can be installed in most weather conditions. The trays are suitable to be used with slates, concrete flat and profile tiles.

Hip accessories:

- Hip Trays 1200mm
- Short tile clips
- Long tile clips

Kit contents

- 13 flexible ridge unions
- 26 ridge clips
- 13 clamps
- 13 screws
- 1 ventilated ridge roll (6m x 300mm)
- 10 ridge batten straps



Dry Ridge Ventilation System Black

Article number: 294350

Compliance, safety and regulation

NB: Please consult a professional building design engineer in case of higher buildings, hilly sites and/or exceptional wind loads e.g. in North West Scotland (zone IV) for detailed evaluation and/or reinforcement instructions.

Maximum peak velocity pressure $q = 1800\text{Pa}$ The Dry ridge union kit complies with BS5250 and provides a high level of ventilation and a good resistance to wind uplift. Suitable for roof pitches up to 55° . It has also been independently tested at the BRE to meet BS8612. Test results from the BRE BS8612 indicate that the dry ridge kit is suitable for use within all wind zones in the United Kingdom. For specific location details please contact Ubbink UK. Complies with BS5250, BS5534 and BS8612.

Technical specifications

Technical	
Colour	Black
Dimensions	
Length gross	NaN
Width	6,000 mm
Height	NaN
Net weight	3.33 kg