

Roll Out Rafter Tray (RB100)



Build smart.

Introduction

RB100 Roll Out Insulation Rafter Tray provides a minimum 25mm clear airway between the ceiling insulation and the roof underlay and is suitable for use in cold roofs, but not suitable for warm roof voids. It is used in conjunction with eaves ventilation products.

Product features and benefits

- Universal rafter centre fitting capability
- Provides a minimum 25mm clear airway
- Available in 6m lengths and optional widths
- Quick and easy to install with no special tools required

Application

- Tiled and slated pitched roofs (insulation at ceiling level)
- Used in conjunction with eaves ventilation products

Dimensions

- L: 6m x W: 300mm (limited stock available)
- L: 6m x W: 400mm (limited stock available)
- L: 6m x W: 600mm
- L: 6m x W: 800mm
- L: 6m x W: 900mm
- L: 6m x W: 1000mm
- L: 6m x W: 1200mm

Weight

- 300mm - 0.5kg per unit
- 400mm - 0.94kg per unit
- 600mm - 1.38kg per unit
- 800mm - 1.5kg per unit
- 900mm - 1.62kg per unit
- 1000mm - 1.82kg per unit
- 1200mm - 1.95 per unit



Colours

- Black

Product Code

- 300mm - 611200
- 400mm - 611210
- 600mm - 611220
- 800mm - 611230
- 900mm - 611240
- 1000mm - 611250
- 1200mm - 611270

Packaging

- All sizes are packed x10 per box

Material

- PVC-U